



**SEWERLOCK™**

**DAVE ROSS**

**(408) 761-5882**

[dave@sewerlock.com](mailto:dave@sewerlock.com)

**OPERATION & MAINTENANCE  
MANUAL**

**SEWER – STORM – WATER - UTILITY  
SECURITY - INFLOW REDUCTION – ODOR  
CONTROL**

**Installed in New and Existing MH  
Fits All Maintenance Holes**

**OPERATION**



**1) REMOVE CAST IRON COVER.**



**2) REMOVE PADLOCKS, TURN EYEBOLTS  
TO ALIGN WITH SLOTS IN INNER COVER,  
AND LIFT OUT THE INNER COVER.**



**3) WHEN WORK IS COMPLETE, ALIGN EYE  
BOLTS WITH THE SLOTS IN THE INNER  
COVER, REPLACE THE INNER COVER,  
AND SECURE THE PADLOCKS.**



**FOR MANHOLES WITH OPTIONAL ODOR  
CONTROL RING WITH PRESSURE SEAL,  
BEFORE REMOVING THE INNER COVER, AIR  
TEST FIRST USING THE BULKHEAD.**

**MAINTENANCE**

*Inspection (Semiannual)*

*Cleaning (At time of Inspection) Lubricate or replace padlocks as needed.*

*Safety (Follow current industry standards)*